

Daudzums	Apraksts
----------	----------

1	SBA 3-35 A
---	------------



Piez me. Produkta att Is var atš irties no faktisk produkta izskata.

Produkta Nr.: [97896286](#)

Grundfos SBA 3-35 A is an all-in-one submersible booster designed for pumping clean water for domestic use. The SBA is built on the proven SB platform and comes with an integrated control unit. This eliminates the need for an external pump controller in the house. It is silent when submerged and therefore a noiseless alternative to surface-mounted pumps. The pump is built from high quality composite and stainless steel materials that are resistant to corrosion.

The SBA 3-35 A is equipped with a 15 m supply cable, and the maximum installation depth is 10 m below the water level, with a liquid temperature ranging from 0 °C to 40 °C.

The pump starts automatically when the pipe pressure falls below 2.2 bar.

The SBA 3-35 A is ideal for operation in a well or ground tanks, as it easily prevents solid particles from entering the pump. The maximum particle size is 1 mm.

The pump features a float switch, which promises the user a convenient experience with automatic start/stop operation of the pump and provides dry running protection.

The single-phase model is effectively protected against any accidental overload by built-in thermal protection.

The pump has built-in thermal protection, which immediately stops the pump if it overheats. Having cooled down, the pump automatically restarts when it reaches a normal temperature.

## Daudzums | Apraksts

### Š idrums:

S kn jamais š idrums: dens  
Š idruma temperat ras diapazons: 0 .. 40 °C  
izv l t š idruma temperat ra: 20 °C  
Bl vums pie izv l t s š idruma temperat ras: 998.2 kg/m<sup>3</sup>

### Tehn.:

Nomin l pl sma: 2.76 m<sup>3</sup>/h  
Nomin lais spiedienaugstums: 25.2 m  
Maks. da i as: 1 mm  
L knes tolerance: ISO9906:2012 3B  
Pretv rstis: YES  
Adjustable start pressure: N  
Iesl gšanas spiediens: 1.5 b ri  
Rated driver speed: 2800 apgr./min

### Materi li:

S k a korpuss: Composite  
Darbrats: Composite

### Uzst d šana:

Apk rt j s vides temperat ras diapazons: -10 .. 50 °C  
Type of inlet connection: STRAINER  
S k a izpl des kan ls: G 1"  
Maksim lais uzst d šanas dzi ums: 10 m

### Elektriskie dati:

Jaudas izlietojums P1: 0.8 kW  
Rated power - P2: 0.54 kW  
T kla frekvence: 50 Hz  
Nomin lais spriegums: 1 x 220-240 V  
Nomin l str va: 3.8 A  
Iesl gšanas str va: 12 A  
Jaudas koeficients: 0.94  
Kondensatora lielums - darb ba: 13 μF/450 V  
Korpasa klase (IEC 34-5): IP68  
Insulation class (IEC 85): F  
Built-in motor protection: YES  
Length of cable: 15 m  
Kabe a veids: H07RN-F 3G1  
Kabe uzga a tips: SCHUKO

### Citi:

Neto svars: 9.42 kg  
Bruto svars: 10 kg  
Pie g des apjoms: 0.022 m<sup>3</sup>  
Danish VVS No.: 391367035  
Swedish RSK No.: 5850417  
Finnish LVI No.: 4822596  
Norwegian NRF no.: 9041873  
Apstiprin jumi: CE, VDE, WEEE  
Izcelsmes valsts: IT  
Muitas tarifa Nr.: 84137029

Apraksts	Vērtība
<b>Vispārīgā informācija:</b>	
Produkta nosaukums:	SBA 3-35 A
Produkta Nr.:	<a href="#">97896286</a>
EAN numurs:	5710626001712
	5710626001712
Cena:	553,20 EUR
<b>Tehniskie dati:</b>	
Nominālā plūsma:	2.76 m³/h
Nominālais spiedienaugstums:	25.2 m
Maksimālais spiedienaugstums:	34 m
Darbrati:	3
Maksimālā diametra caurule:	1 mm
Līknes tolerance:	ISO9906:2012 3B
Pretvēršanās:	YES
Adjustable start pressure:	N
Ieslēgšanas spiediens:	1.5 bar
Rated driver speed:	2800 apgr./min
<b>Materiāli:</b>	
Sūkņa korpusa materiāls:	Composite
Darbratu materiāls:	Composite
<b>Uzstādīšana:</b>	
Apkārtojamās vidējās temperatūras diapazons:	-10 .. 50 °C
Type of inlet connection:	STRAINER
Sūkņa izplūdes caurules diametrs:	G 1"
Maksimālais uzstādīšanas dziļums:	10 m
<b>Šķidrums:</b>	
Sūkņa jāmācītais šķidrums:	dens
Šķidruma temperatūras diapazons:	0 .. 40 °C
Izvērtējuma temperatūra:	20 °C
Būvniecības pieļaujamais šķidruma temperatūras diapazons:	998.2 kg/m³
pH vērtības diapazons:	4-9
<b>Elektriskie dati:</b>	
Jaudas izlidojums P1:	0.8 kW
Rated power - P2:	0.54 kW
Tīkla frekvence:	50 Hz
Nominālais spriegums:	1 x 220-240 V
Nominālā strāva:	3.8 A
Ieslēgšanas strāva:	12 A
Jaudas koeficients:	0.94
Kondensatora lielums - darbība:	13 µF/450 V
Korpusa klase (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	YES
Length of cable:	15 m
Kabeļa veids:	H07RN-F 3G1
Kabeļa uzgādes tips:	SCHUKO
<b>Kontrole:</b>	
PI sīmas slēdzis:	j
<b>Citi:</b>	
Neto svars:	9.42 kg
Bruto svars:	10 kg
Piegādes apjoms:	0.022 m³
Danish VVS No.:	391367035
Swedish RSK No.:	5850417
Finnish LVI No.:	4822596
Norwegian NRF no.:	9041873
Apstiprinājumi:	CE, VDE, WEEE
Izcelsmes valsts:	IT
Muitas tarifa Nr.:	84137029

